

SPECIFICATION

Model: EW750DST		Protect Class: IP23	
Insulation Class: F		Noise Level:71dB(7m)	
W E L D E R	CC OUTPUT		
	Rate Output	KW	13.4×2
	Rated Amp.(Dual)	A	380×2
	Rated Amp.(Single)	A	650
	Rated Volt.	V	35.2
	No-load Volt.	V	85
	Duty Cycle	%	60
	Current Range(Dual)	A	60~400
	Current Range(Single)	A	60~700
	CV OUTPUT (OPTIONAL)		
	No-load Volt.	V	22-43
	Rated Output	KW	11×2
	Rated Amp.	A	350×2
	Rated Volt.	V	31.5
	Duty Cycle	%	80
G E N E R A T O R	Rate Output	KVA	30
	Rated Volt.	V(AC)	120/220/380
	Rated Amp.	A	45
	Phase	—	3-phase, 4-wire
	Power factor	%	80
	Frequency	Hz	50/60
	Brushless	—	Yes
Driven	—	Direct Couple	
E N G I N E	Name	—	DEUTZ TD226B
	Type	—	4-stroke, 3-cylinder
	Displacement	L	3.12
	Rated Output	KW	45
	Rated speed	rpm	1500/1800
	Starter	—	Electric, 24V
	Fuel	—	Light diesel
Coolant	—	Water-cooled	
O T H E R S	Fuel tank	L	79
	Battery	—	(12V-100AH)×2
	Dimension	mm	2000×900×1000
	Dry weight	KG	1200